



Picking to packing

Crop care

Harvest & transport

Crop protection

Handling systems

Components

Service & maintenance

BRW150 pipe rail trolley

We offer you:

- Simple working height adjustment
- Special spray trolley version
- Flexible use in all conditions
- Electronic motor control for maximum control



Since the introduction of the pipe rail system, pipe rail trolleys have become indispensable in greenhouses. Through the years, there has been further improved the BRW150 in terms of both mechanics and electronics. What remains is the ease with which employees can carry out their tasks ergonomically and efficiently without damaging the crops. Optimisations is found in the simple controls, the motor power control and options for increasing the working level. A special version is the spray trolley, which is equipped with a stronger 0.37 kW motor.

BRW150 pipe rail trolley





The basis is a standard, robust pipe rail trolley whose working platform can be expanded with a safety railing, hand scissors and detachable platforms in combination with fixed steps.



The SW08 spray trolley is a special version with a stronger 0.37 kW motor and a motor control for the mounted reel.



The control post can be adjusted in height from 195 cm to 250 cm. This in connection with the possible mounting of manually adjustable scissors.



Thanks to the electronic motor control in combination with strong traction batteries, sufficient power is also available at low speeds and for a longer period.

Technical specifications of the BRW150		
Length	[cm]	150
Width	[cm]	C/C + 14
Min. platform height	[cm]	20
Max. working height	[cm]	Can be expanded to 230
Motor power	[kW]	0,18
Motor power SW08	[kW]	0,37
Weight	[kg]	110
Speed BRW150	[m/min]	0 - 40
Speed SW08	[m/min]	0 - 70
Traction battery voltage and capacity	[V/Ah]	24/120 (5h) 24/159 (20h)
Rail width	[cm]	42 - 60
Pipe size	[mm]	51
Control post height	[cm]	195 - 250

